

MPG 35kV scope of application

Product legend



Technical Data

Model	Applicable busbar width	Dimension before shrinking		Dimension after shrinking		
		Internal diameter	Wall thickness	Internal diameter	section type	successive type
35kV MPG30	30-40	30 ± 2	2.0 ± 0.3	13	3.5 ± 0.3	3.2 ± 0.3
35kV MPG40	40-50	40 ± 2	2.0 ± 0.3	15	3.5 ± 0.3	3.2 ± 0.3
35kV MPG50	50-60	50 ± 2	2.0 ± 0.3	20	4.0 ± 0.3	3.2 ± 0.3
35kV MPG60/65	60-70	65 ± 2	2.0 ± 0.3	24	4.0 ± 0.3	3.2 ± 0.3
35kV MPG80	80-100	80 ± 3	2.2 ± 0.3	32	4.0 ± 0.3	3.2 ± 0.3
35kV MPG100	100-120	100 ± 4	2.5 ± 0.3	40	4.0 ± 0.3	3.2 ± 0.3
35kV MPG120	150	120 ± 4	2.5 ± 0.3	48	4.5 ± 0.3	3.2 ± 0.3
35kV MPG150	200	150 ± 4	2.5 ± 0.3	60	4.5 ± 0.3	3.2 ± 0.3
35kV MPG180	max	180 ± 5	2.5 ± 0.3	70	4.5 ± 0.3	3.2 ± 0.3
35kV MPG210	max	210 ± 5	2.5 ± 0.3	80	4.5 ± 0.3	3.2 ± 0.3